



CHEYENNE REFINERY  
 P O BOX 1588  
 CHEYENNE, WYOMING 82003  
 PRODUCT SPECIFICATIONS  
 PRODUCT NAME: TS2 (Truckstop) ULSD w/additive

ASTM PROPERTY	ASTM TEST METHOD	SPECIFICATION	
		MIN.	MAX.
Appearance @ 70°F	Visual	Bright/Clear	
Gravity, Degrees A.P.I.	D 287	30	
Colonial Haze	Visual		3
Distillation (760 mm Hg) 90%	D 86	540	640
Flash Point, Deg F, PM	D 93	130	
Color, ASTM	D 1500		2
Corrosion, CST, 3 hrs @ 212 °F	D 130		1
Sulfur, ppm	D 5453		15
Ash, wt %	D 482		0.01
Carbon Ramsbottom, 10% Bottom, %	D 524		0.35
Pour Point, Deg. F. Summer: March 1 - August 31 TS2 Winter: Sept. 1- February 28	D 97		Report -15
Cloud Point, Degrees F. Summer: April 1 - August 31 Winter: Sept. 1 - February 28 * March (transitional period)	D 2500, 3117, or 5773		16 6 10
Cold Filter Plug Point (CFPP) Winter only – Cheyenne	EN 116		-25
Water & Sediment, vol %	D 1796		0.05
Viscosity, @ 100 ° F. CST	D 445	1.9	4.1
Cetane Index - Cheyenne	D 976	42	
Cetane Index – Calculated for Kaneb Pipeline at Rapid City, Dupont and Fountain	D 976	42	
Thermal Stability, 90 minutes 300 f DuPont Scale			4
Lubricity, Wear Scar Diameter (microns)	D 6079		520
Conductivity at ambient temperatures (pS/m)	D 2624	50	

This product, when dyed red, may be sold for non-taxable use only - penalty for taxable use.

SPECIFICATIONS
----------------

Meets Specification: EPA 40 CFR 80.29

Effective October 15, 2006